

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (Currently Amended) An arrangement used for securing a fan frame to a heat exchanger, comprising:

a first heat exchanger comprising a tube/rib block, a first header and a second header, ~~at least one header with holders, and a snap hook~~, and

a fan frame comprising a framework with a first set of projections, a second set of projections, and at least one rib,

wherein the first header has holders and the second header has snap hooks,

wherein the holders and the first set of projections are configured to be in operative contact with one another at securing points,

wherein the at least one rib is configured to stiffen the framework, and

wherein each one of the snap hooks ~~hook~~ passes through a corresponding one of the second set of projections and engages with the ~~projection~~ corresponding one of the second set of projections.

2 -27. (Cancelled)

28. (Previously Presented) The arrangement as claimed in claim 1, further comprising at least one additional heat exchanger comprising projections.

29. (Currently Amended) The arrangement as claimed in claim 28, wherein the first heat exchanger further comprises securing tenons,

wherein the fan frame and the at least one additional heat exchanger each comprises at least one supporting device,

wherein the securing tenons of the first heat exchanger are configured to support the first heat exchanger on an abutment, and

wherein the at least one supporting device of the fan frame and the at least one supporting device of the at least one additional heat exchanger are configured to support the fan frame and the at least one additional heat exchanger, respectively, on the abutment and

the first set of projections.

30. (Previously Presented) The arrangement as claimed in claim 29, wherein the securing tenons and the supporting device of the fan frame and/or of the additional heat exchangers are arranged in a common securing region and are integrated in one another.

31. (Previously Presented) The arrangement as claimed in claim 29, wherein the abutment is part of a motor vehicle framework.

32. (Currently Amended) The arrangement as claimed in claim 28, wherein the fan frame and/or the additional heat exchanger ~~exchangers~~ are secured solely to the first and second headers ~~header~~ of the first heat exchanger.

33. (Currently Amended) The arrangement as claimed in claim 28, wherein the first and second headers ~~are header~~ is arranged laterally on the first heat exchanger, and the projections are arranged laterally on the fan frame, ~~and/or the additional heat exchanger.~~

34. (Currently Amended) The arrangement as claimed in claim 28, wherein the first set of projections of the fan frame ~~and/or of the additional heat exchangers~~ and the holders of the first header are configured to be inserted and/or latched into one another.

35. (Currently Amended) The arrangement as claimed in claim 1, wherein the first and second ~~heat exchanger has another header such that the two~~ headers are arranged on opposite sides of the first heat exchanger.

36. (Currently Amended) The arrangement as claimed in claim 35, wherein the rib of the fan frame is arranged between the first and second ~~[[two]]~~ headers of the first heat exchanger.

37. (Currently Amended) The arrangement as claimed in claim 35, wherein the rib has a length which corresponds to the distance between the first and second ~~[[two]]~~ headers.

38. (Previously Presented) The arrangement as claimed in claim 1, wherein the rib has a depth which corresponds approximately to a depth of the tube/rib block of the heat exchanger.

39. (Previously Presented) The arrangement as claimed in claim 1, wherein a depth of the rib is variable along the rib and has a maximum depth at mid-length of the rib.

40. (Previously Presented) The arrangement as claimed in claim 1, wherein the at least one rib covers the tube/rib block of the first heat exchanger.

41. (Previously Presented) The arrangement as claimed in claim 1, wherein the fan frame is produced as a plastic part and the at least one rib can be injection-molded onto the framework.

42. (Currently Amended) The arrangement as claimed in claim 1, ~~wherein the at least one header comprises a first header and a second header, wherein the first header has the holders and the second header has the snap hooks, wherein the holders of the first header comprise insertion orifices, wherein the first set of projections comprises comprise insertion tabs on one side of the fan frame and the second set of projections comprises comprise~~ securing tabs with latching orifices on the opposite side, and wherein the insertion tabs are configured for insertion into the insertion orifices such that the fan is configured to be subsequently folded and latched by the snap hooks engaged with the securing tabs.

43. (Currently Amended) The arrangement as claimed in claim 1, wherein the fan frame further comprises ribbed feet injection-molded onto a lower region of the framework, wherein the first and second headers further comprise ~~at least one header further comprises~~ reception orifices, and wherein the feet can be received into the reception orifices.

44. (Currently Amended) The arrangement as claimed in claim 43, wherein lower snap hooks are arranged on the feet and edges are arranged on the reception orifices such that the lower snap hooks that are arranged on the feet can be latched with the edges.

45. (Currently Amended) The arrangement as claimed in claim 1, wherein the fan frame further comprises ribbed feet injection-molded onto a lower region of the framework, wherein the first and second headers further comprise ~~at least one header further comprises~~ reception orifices, and wherein one of the feet received into one of the reception orifices forms a fixed bearing, and another of the feet received into another of the reception orifices

forms a loose bearing.

46. (Currently Amended) The arrangement as claimed in claim [[1]] 29, wherein the fan frame further comprises ribbed feet injection-molded onto a lower region of the framework, wherein the first and second headers further comprise at least one header further comprises reception orifices, and wherein the securing tenons are arranged below the reception orifices.

47. (Previously Presented) The arrangement as claimed in claim 1, wherein the heat exchanger is a coolant cooler.

48. (Previously Presented) The arrangement as claimed in claim 47, wherein the coolant cooler is part of a cooling module for a motor vehicle.

49. (Currently Amended) The arrangement as claimed in claim 1, A fan frame for an arrangement as claimed in claim 1, comprising a wherein the framework with an comprises an approximately rectangular horizontal cross section.